

SalvisLab Vacucenter – Heating Technology with Swiss Precision




swiss made +

salvisLAB

SalvisLab Vacucenter – versatile and precise

Vacuum dryer for delicate goods

The SalvisLab Vacucenter represents the optimal solution for oxidation-sensitive substances and thermally instable products. It provides precise thermal conditions in dust-free vacuum atmosphere. These characteristics enable highly successful SalvisLab Vacucenter applications for a wide range of laboratory applications in areas such as chemical engineering, pharmaceuticals, foodstuffs, cosmetics and electronics. The carefully designed wall heating system may be controlled to within 0.1°C and ensures stable temperature conditions over the entire Vacucenter chamber ranging up to + 200°C.



■ **GLP/GMP conformity**
SalvisLab Vacucenters meet GLP and GMP standards.



■ **Safety on all levels**

The Vacucenters feature an exclusive pressure safety system with door safety catch. The sight window consists of double pane safety glass. Heating without vacuum is prevented by means of a pressure threshold switch. Upon door opening, the heating system is immediately turned off. SalvisLab Vacucenters are classified in Safety Class 3.1.



■ Turbulence-free return to ambient atmosphere

Return to atmospheric pressure is enabled by means of a precision needle valve for ambient air or inert gas. A cleverly designed input jet behind a fender plate permits pressurisation of the chamber without causing turbulence.



■ SalvisLab EasyMenu with vacuum level control

In a series of easy to comprehend steps, the exclusive SalvisLab EasyMenu leads the user through application and programming of the Vacucenter. The PID controller featuring fuzzy logic characteristics controls temperature, timing and even the evacuation level. Fifty programs consisting of 15 program steps each are at your disposal for a program duration of up to 999 hours.



■ Easy cleaning



For cleaning purposes, the insert brackets may be removed with just a few easy steps. Inside the chamber, all transitional areas between walls, ceiling and chamber floor are designed with convenient radii to enable easy and efficient cleaning.

■ High Quality Design

The chamber interior as well as ducting and valves are made of high quality stainless steel. The insert panels consist of anodised aluminium, thus enabling efficient heat transfer and best resistance for chemicals.



Technical Data SalvisLab Vacucenter



■ Pressure and temperature performance

Constant chamber temperature and vacuum level are made possible by means of a door seal made of Silicon or Viton™. To maintain proper performance, the door seal may easily be removed for cleaning.

SalvisLab Vacucenter	VC20	VC50
Useable volume (l)	20	50
Max. Temperature (°C)	200	200
Outside dimensions (WxHxD) mm	545x375x425	645x475x525
Inside dimensions (wxhxd) mm	250x250x320	350x350x420
Weight (kg)	34	56
Shelves (standard/max.)	1/3	1/5
Shelf load max. (kg)	20	20
Voltage ±10% (V)	230/115	230/115
Temperature variation at 100°C (±°C)	1.7	1.7
Temperature fluctuation at 100°C (±°C)	0.2	0.2
Microprocessor PID controller	•	•
Alphanumeric LCD display illuminated	•	•
Programming	•	•
- Programs x steps	50 x 15	50 x 15
- Temperature, time, gradient	•	•
Timer (h)	999	999
RS232/RS422 interface	•/optional	•/optional
Digital vacuum indication or control	optional	optional
Vacuum pump	optional	optional
Safety class	3.1	3.1

Note: technical data subject to change without prior notice.

swiss made +

salvisLAB

Manufacturer:
E. Renggli AG
Industrie-Ost
CH-6343 Rotkreuz (Switzerland)
Phone ++41 (0)41 798 14 44
Fax ++41 (0)41 790 38 03
salvislab@renggli.com
www.salvislab.com